

Introduction

Anda NM (31Ah-250Ah) series is designed for standby use with 10-year design life in float service. The series battery is featured of high consistency, excellent performance and reliable standby service life. It is widely applied in float service, UPS/EPS, medical equipment, telecom, photovoltaic, control system and security system.

Battery Features

- Increase durability and deep cycle ability for heavy demand applications
- Low self-discharge
- Fully tank formed plates
- Low impurity electrolyte
- Spill proof / leak proof
- Multi-position usage
- ABS case and cover VO upon request
- Very high purity lead

Electrical Specification

Design floating Life @ 20°C (68°F)	10 years
Nominal Capacity @ 25°C /77°F	
20 hour rate 2.82A to 1.75Vpc	56.4 Ah
10 hour rate 5.5A to 1.75Vpc	55 Ah
Internal Resistance	
(Fully charged battery @ 25°C /77°F)	7mΩ
Max. Discharge Current @ 25°C /77°F	550 A (5S)
Charge Methods: Constant voltage charge @ 25°C /77°F	
Cycle Use	14.7 ~ 14.9V
Max. Current	14 A
Standby Use	13.6 - 13.8V
Operating Temperature Range	-30 ~ 50°C
<i>Notes: battery voltage must be adjusted according to temperature. Please refer to our recommendation.</i>	
Self-Discharge	
3% of capacity declined per month @ 25°C (77°F).	

Battery Picture & Terminal Layout



Dimension & Weight

Length	Dimension (± 2mm)			Total Height	Weight (± 2%)
	Width	Height	Height		
229 mm	137 mm	210 mm	215 mm	16.5 kg	
9.0 inch	5.4 inch	8.3 inch	8.5 inch	36.4 lbs	

Typical Applications

- Telecommunications
- Power Utility
- Data Center
- UPS & EPS

Certificates



Constant Current Discharge (Amperes @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	126.7	96.74	83.57	70.40	59.59	55.13	51.41	47.69	44.59	42.29	40.30	21.85	15.54	12.91	10.56	5.64	2.85
1.65	120.3	91.86	79.79	67.71	57.99	53.67	50.14	46.60	43.68	41.56	39.75	21.42	15.25	12.64	10.31	5.61	2.85
1.70	115.4	88.07	76.64	65.21	56.13	51.90	48.50	45.10	42.32	40.33	38.65	20.70	14.90	12.34	10.07	5.56	2.85
1.75	110.0	84.00	73.22	62.43	54.00	49.94	46.77	43.60	41.05	39.28	37.83	20.13	14.57	12.07	9.85	5.50	2.82
1.80	104.4	79.67	69.62	59.57	51.87	47.93	44.95	41.96	39.60	38.00	36.74	19.40	14.22	11.77	9.61	5.36	2.80

Constant Power Discharge (Watts/cell @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	235.5	179.8	158.2	136.6	117.9	107.4	99.81	92.17	85.14	79.20	73.66	40.85	30.02	25.09	20.67	11.58	6.11
1.65	227.2	173.4	152.9	132.4	114.7	104.6	97.25	89.90	83.15	77.50	72.25	40.01	29.74	24.82	20.39	11.47	6.11
1.70	218.4	166.7	147.2	127.7	111.0	101.3	94.31	87.35	80.98	75.71	70.85	39.03	29.19	24.38	20.08	11.24	6.03
1.75	208.9	159.5	141.1	122.7	107.1	97.7	91.09	84.51	78.52	73.64	69.16	37.76	28.35	23.78	19.72	11.16	5.92
1.80	198.7	151.7	134.4	117.2	102.8	93.8	87.59	81.39	75.79	71.29	67.19	36.40	27.60	23.19	19.27	11.05	5.86

Graphs

